IN THE CLAIMS

Please amend the claims as follows:

Claims 1-12 (Canceled).

Claim 13 (Previously Presented): A process for preparing a toner comprising:

pulverizing a resin composition with a jet type pulverizer comprising a venturi nozzle and an impact member arranged so as to face the venturi nozzle,

wherein the impact member is a cylindrical member of which a bottom is in a form of a part of a true circle or an oval, wherein the cylindrical member comprises an impact side on a curved side, and the impact side faces toward an inlet of the venturi nozzle, and

wherein an axis of the cylindrical member is disposed at a non-zero angle relative to a longitudinal axis of the venturi nozzle.

Claim 14 (Previously Presented): The process according to claim 13, wherein the impact member is arranged to face an outlet of the nozzle so that a most projected part is located on an extension of a central shaft of the venturi nozzle.

Claim 15 (Previously Presented): The process according to claim 13, wherein the venturi nozzle comprises an inlet, a throat part, a diffuser part, and an outlet in that order, wherein an inner side of said throat part forms a smooth, continuous arc starting from the inlet to the diffuser part.

Claim 16 (Previously Presented): The process according to claim 13, wherein the venturi nozzle comprises an inlet, a throat part, a diffuser part, a straight part, and an outlet in that order.

Claim 17 (Previously Presented): The process according to claim 13, wherein the resin composition is mixed with a fine inorganic particle, and thereafter the mixture is fed to

the jet type pulverizer.

Claim 18 (Previously Presented): The process according to claim 17, wherein the fine

inorganic particle is made of silica.

Claim 19 (Previously Presented): The process according to claim 13, wherein the

resin composition comprises a resin binder comprising at least one member selected from the

group consisting of polyesters, vinyl resins such as styrene-acrylic resins, epoxy resins,

polycarbonates, polyurethanes, and a hybrid resin in which two or more resin components are

partially chemically bonded.

Claim 20 (Previously Presented): The process according to claim 13, wherein the

resin composition is a resin composition having a particle size of 3 mm or less, obtained by

melt-kneading a mixture comprising a resin binder and a colorant, and thereafter pulverizing

the mixture.

Claim 21 (Previously Presented): The process according to claim 13, wherein the

toner has a volume-average particle size of 7 μm or less.

Claim 22 (Canceled).

Claim 23 (Withdrawn-Currently Amended): A jet type pulverizer comprising:

4

a venturi nozzle; and

an impact member arranged so as to face the venturi nozzle,

wherein the impact member is a cylindrical member of which bottom is in a form of a part of a true circle or an oval, wherein the cylindrical member comprises an impact side on a curved side and the impact side faces toward an inlet of the venturi nozzle, and

wherein an axis of the cylindrical member is disposed at a non-zero angle relative to a longitudinal axis of the venturi nozzle.

Claim 24 (Previously Presented): The process according to claim 13, wherein the non-zero angle is a right-angle.

Claim 25 (Previously Presented): The process according to claim 13, further comprising arranging the axis of the cylindrical member horizontally with respect to gravity, wherein the direction of the impact of the product to be pulverized is parallel to a horizontal surface of the cylindrical member.